



# Quality







## *Quality* Bale Moving Equipment

King Kutter Bale Moving Equipment is built with farmers in mind. They are engineered with high quality forged penetrator spears and durable stabilizer spikes that slide easily into bales of hay, minimizing damage to the bale. The tapered forks of the E-511 are designed to minimize field damage, and slide smoothly under bales. Whether you need a 3-pt. Spear Penetrator, a Bucket Spike, a Bale Mover, Universal Bale Spear, or a Skid Steer Spear, King Kutter has the Bale Moving Equipment you need.



### ***Bucket Spike***

- Loader bucket attachment.
  - Specially designed penetrator spear
  - Standard bale stabilizer points
  - Rated for Bales up to 2,000 lbs.
- (Model: BS-325)



### ***3-pt. Spear Penetrator***

- Cat. I or II step up pin straddle hitch.
  - Specially designed penetrator spear
  - Standard bale stabilizer points
  - Rated for Bales up to 2,000 lbs.
- (Model: RS-500)





# Val Treatment

## Quick Hitch Compatible



### **Bale Mover**

- Cat. I or II step up pin straddle hitch
- Specially designed tapered forks minimize bale and field damage
- Rated for Bales up to 2,000 lbs.  
(Model: E-511)



### **Universal Bale Spear**

- Unique universal hitch will accept Cat. I or Cat. II 3-pt. hitch or mount to most front loaders
- Specially designed penetrator spear
- Standard bale stabilizer points
- Rated for Bales up to 2,000 lbs.  
(Model: F-602)



### **Skid Steer Spear**

- Quick attach Skid Steer mount
- Specially designed penetrator spear
- Standard bale stabilizer points
- Rated for Bales up to 2,000 lbs.  
(Model: SSS)





# Bale Moving Equipment Specifications

<b>Model</b>	RS-500	F-602
Approx. Weight	103 lbs.	204 lbs.
<b>Performance</b>		
Weight Rating	2,000 lbs.	2,000 lbs.
Penetrator Spear	Forged Steel	Forged Steel
Penetrator Attachment	Bolt-on, Tapered Nut & Bushing	Bolt-on, Tapered Nut & Bushing
No. of Stabilizer Spikes	2 Beveled	2 Beveled
<b>Construction</b>		
Hitch	Cat. I & II	Cat. I & II 3-pt Hitch & Front Loader
Hitch Type	Clevis	Clevis
Quick Hitch Compatible	Yes, Cat. I	No
Frame	Tube & Flat Steel	Tube & Flat Steel

<b>Model</b>	BS-325
Approx. Weight	90 lbs.
<b>Performance</b>	
Weight Rating	2,000 lbs.
Penetrator Spear	Forged Steel
Penetrator Attachment	Bolt-on, Tapered Nut & Bushing
No. of Stabilizer Spikes	2 Beveled
<b>Construction</b>	
Attachment	Loader Bucket
Frame	Angle & Flat Steel

<b>Model</b>	SSS
Approx. Weight	200 lbs.
<b>Performance</b>	
Weight Rating	2,000 lbs.
Penetrator Spear	Forged Steel
Penetrator Attachment	Bolt-on, Tapered Nut & Bushing
No. of Stabilizer Spikes	2 Beveled
<b>Construction</b>	
Attachment	Skid Steer Loader Type
Frame	Tube, Flat Steel, & Channel

<b>Model</b>	E-511
Approx. Weight	191 lbs.
<b>Performance</b>	
Weight Rating	2,000 lbs.
Bale Forks	Dual, Tapered
<b>Construction</b>	
Hitch	Cat. I & II
Hitch Type	Clevis
Quick Hitch Compatible	Yes
Frame	Tube & Flat Steel

\*Specifications also available at [www.kingkutter.com](http://www.kingkutter.com).

\*Weights are for products only. Does not include packaging material.

**King Kutter Inc.**

PO Box 1200

Winfield, AL 35594

205.487.3202

[www.kingkutter.com](http://www.kingkutter.com)

**Quality Rotary Mowers & Farm Equipment**

King Kutter, Inc. reserves the right to change model numbers, optional equipment and product specifications without notice.

**KingKutter®**  
INCORPORATED