





Quality Disc Harrows

Quality is an important word at King Kutter. It's who we are. It's what we do. It's the equipment we build. Landscapers, Nursery Owners, Farmers, and Homeowners can get the job done fast, and do a job they can be proud of with a Disc Harrow from King Kutter.

Tough field conditions demand a tough King Kutter Disc Harrow. We have three styles to choose from, the quick hitch compatible Angle Frame and Box Frame Disc Harrows and the XB Sub-Compact Angle Frame Disc Harrow. Our Discs are built with the quality and features that will help turn your "dirt" into fertile "soil" for growing grass, vegetables, flowers, or any number of plants. Choose combination blades (notched front & smooth rear) for most applications. King Kutter Disc Harrows are also available with notched blades (front & rear) to manage heavy plant residue. King Kutter Disc Harrows are rugged. Heavy blades, precision bearings, tough angle frames or durable box frames and working widths of 4 1/2' to 7 1/2', ensure King Kutter has the right Disc Harrow for you.



Box Frame Construction



Angle Frame Construction



XB Sub-Compact Model



Get more work out of your sub-compact tractor with the King Kutter XB Sub-Compact Angle Frame Disc. This disc for sub-compacts has all the quality and features of a full size disc. The heavy angle frame and front and rear notched disc blades produce a better seed bed. Heavy duty greaseable bearings will provide years of service.



The Perfect Disc For Your Sub-Compact Tractor



XB Sub-Compact
Angle Frame Disc

Limited Cat. I, 3-pt hitch, 16 blades, 14" diameter,
Notched blades (front & rear). Horsepower range: Up to 25



Model shown: 18-20-G-C

King Kutter's Angle Framed Discs are field-tested and built to last. They are quick hitch compatible, available in two disc blade sizes (16" or 18"), two disc blade styles (notched or smooth), and widths of (4-1/2', 5-1/2', & 6-1/2').

Quick Hitch
Compatible



Choose from three sizes:

- 4 1/2' Angle Frame Discs - 12 blades,
16" diameter combination blades (notched front & smooth rear),
or notched blades (front & rear), quick hitch compatible.
(Model: 16-12-G-C & 16-12-G-N)
- 5 1/2' Angle Frame Discs - 16 blades, 16"
or 18" diameter combination blades (notched front & smooth rear),
or notched blades (front & rear), quick hitch compatible.
(Model: 16-16-G-C, 16-16-G-N, 18-16-G-C, & 18-16-G-N)
- 6 1/2' Angle Frame Discs - 20 blades, 16"
or 18" diameter combination blades (notched front & smooth rear),
or notched blades (front & rear), quick hitch compatible.
(Model: 16-20-G-C, 16-20-G-N, 18-20-G-C, & 18-20-G-N,)



Bolt Style Gang Adjustment



Combination Blades



Excellent Soil Finish





Model shown: 18-20-G-CBF

King Kutter's Box Frame Discs are heavy duty discs that are built to last. Available in two blade sizes 18" or 20", and widths of 5-1/2', 6-1/2', & 7-1/2'. Two disc styles are available, notched or combination (notched front & smooth rear). All Box Frame Discs are Cat. I quick hitch compatible

QuickHitch
Compatible



Choose from three sizes:

5 1/2' Box Frame Discs - 16 blades, 18" diameter, combination blades (notched front & smooth rear) or notched blades (front & rear), quick hitch compatible.
(Model: 18-16-G-CBF & 18-16-G-NBF)

6 1/2' Box Frame Discs - 20 blades, 18" or 20" diameter, combination blades (notched front & smooth rear) or notched blades (front & rear), quick hitch compatible.
(Model: 18-20-G-CBF & 18-20-G-NBF, 20-20-G-CBF & 20-20-G-NBF)

7 1/2' Box Frame Discs - 24 blades, 18" or 20" diameter, combination blades (notched front & smooth rear) or notched blades (front & rear), quick hitch compatible.
(Model: 18-24-G-CBF & 18-24-G-NBF, 20-24-G-CBF & 20-24-G-NBF)



Easy Gang Angle Adjustment



Sealed Bearings



Heavy Duty Box Frame



Disc Harrow Specifications

Model	18-16-G-CBF	18-16-G-NBF	18-20-G-CBF / 20-20-G-CBF	18-20-G-NBF / 20-20-G-NBF
Size	5 1/2' Box Frame Disc	5 1/2' Box Frame Disc	6 1/2' Box Frame Discs	6 1/2' Box Frame Discs
HP Range	25 - 45	25 - 45	25 - 60	25 - 60
Approx. Weight	764 lbs.	735 lbs.	857 lbs. / 909 lbs.	823 lbs. / 874 lbs.
Performance				
Working Width	5' 6"	5' 6"	6' 6"	6' 6"
Working Depth*	6" - 8"	6" - 8"	6" - 8" / 7" - 9"	6" - 8" / 7" - 9"
No. of Disc Blades	16	16	20	20
Disc Blade Spacing	7"	7"	7"	7"
Disc Blade Diameter	18"	18"	18" / 20"	18" / 20"
Blade Description	Notched Front, Smooth Rear	Notched	Notched Front, Smooth Rear	Notched
Construction				
Hitch	Cat. I	Cat. I	Cat. I	Cat. I
Quick Hitch Compatible	Yes	Yes	Yes	Yes
Frame	3" Square tubing	3" Square tubing	3" Square tubing	3" Square tubing
Bearings	Sealed, Ball	Sealed, Ball	Sealed, Ball	Sealed, Ball
Gang Angle Adjustment	Bolt	Bolt	Bolt	Bolt
Gang Axle	1" Square	1" Square	1" Square	1" Square

Model	18-24-G-CBF / 20-24-G-CBF	18-24-G-NBF / 20-24-G-NBF	14-16-N-XB	16-12-G-C / 16-12-G-N
Size	7 1/2' Box Frame Discs	7 1/2' Box Frame Discs	5' XB Angle Frame Disc	4 1/2' Angle Frame Discs
HP Range	25 - 60	25 - 60	Up to 25	17 - 30
Approx. Weight	863 lbs. / 1012 lbs.	830 lbs. / 985 lbs.	418 lbs.	405 lbs. / 401 lbs.
Performance				
Working Width	7' 6"	7' 6"	5'	4' 6"
Working Depth*	6" - 8" / 7" - 9"	6" - 8" / 7" - 9"	4" - 5"	5" - 7"
No. of Disc Blades	24	24	16	12
Disc Blade Spacing	7"	7"	7"	7"
Disc Blade Diameter	18" / 20"	18" / 20"	14"	16"
Blade Description	Notched Front, Smooth Rear	Notched	Notched	Notched Front & Smooth Rear / Notched
Construction				
Hitch	Cat. I	Cat. I	Limited Cat. I	Cat. I
Quick Hitch Compatible	Yes	Yes	No	Yes
Frame	3" Square tubing	3" Square tubing	Angle	Angle
Bearings	Sealed, Ball	Sealed, Ball	Greaseable	Greaseable
Gang Angle Adjustment	Bolt	Bolt	Bolt	Bolt
Gang Axle	1" Square	1" Square	1" Square	1" Square

Model	16-16-G-C / 16-16-G-N	18-16-G-C / 18-16-G-N	16-20-G-C / 16-20-G-N	18-20-G-C / 18-20-G-N
Size	5 1/2' Angle Frame Discs	5 1/2' Angle Frame Discs	6 1/2' Angle Frame Discs	6 1/2' Angle Frame Discs
HP Range	17 - 35	17 - 35	20 - 40	20 - 40
Approx. Weight	466 lbs. / 460 lbs.	502 lbs. / 497 lbs.	529 lbs. / 524 lbs.	592 lbs. / 567 lbs.
Performance				
Working Width	5' 6"	5' 6"	6' 6"	6' 6"
Working Depth*	5" - 7"	6" - 8"	5" - 7"	6" - 8"
No. of Disc Blades	16	16	20	20
Disc Blade Spacing	7"	7"	7"	7"
Disc Blade Diameter	16"	18"	16"	18"
Blade Description	Notched Front & Smooth Rear / Notched	Notched Front & Smooth Rear / Notched	Notched Front & Smooth Rear / Notched	Notched Front & Smooth Rear / Notched
Construction				
Hitch	Cat. I	Cat. I	Cat. I	Cat. I
Quick Hitch Compatible	Yes	Yes	Yes	Yes
Frame	Angle	Angle	Angle	Angle
Bearings	Greaseable	Greaseable	Greaseable	Greaseable
Gang Angle Adjustment	Bolt	Bolt	Bolt	Bolt
Gang Axle	1" Square	1" Square	1" Square	1" Square

*Specifications also available at www.kingkutter.com.

*Weights are for products only. Does not include packaging material.

*Working Depth can vary with soil type and conditions.

King Kutter Inc.

PO Box 1200

Winfield, AL 35594

205.487.3202

www.kingkutter.com

Quality Rotary Mowers & Farm Equipment

King Kutter, Inc. reserves the right to change model numbers, optional equipment and product specifications without notice.


KingKutter®
INCORPORATED