





Model shown: DEG-72

Quality Landscape Equipment

Quality is an important word at King Kutter. It's who we are. It's what we do. It's the equipment we build. Landscapers, Nursery Owners, Farmers, and Homeowners can get the job done fast, and do a job they can be proud of with Landscape Equipment from King Kutter.

Landscape your property, build and maintain roads, aerate your lawn, move piles of dirt, or prepare to lay sod with King Kutter Landscaping Equipment. King Kutter Box Blades, Landscape Rakes, Dirt Scoops, and Dual Edge Land Graders, are designed, built, and manufactured to last. We have four styles of Box Blades including the standard BB Series, the Professional and Hinged Back models, and the XB Sub-Compact units. King Kutter also has three styles of Landscape Rakes: the Tubular Frame models, which feature our patented kickstand, a Professional Series, and the XB models designed specifically for Sub-Compact tractors.



All Welded Construction on Hinged Back Box Blades



Individually Mounted Spring Steel Tines



Scoop Dirt



Reversible Dirt Scoop



Model shown: DS-30

King Kutter's Reversible Dirt Scoop is a great tool for moving and transporting dirt and material. The reversible mounting allows you to attach your tractor to the front or the rear of the scoop. The self-leveling pan and trip dump feature allows you to dump and reset the pan without leaving the operator's seat. With an approximate capacity of 9 cu. ft., King Kutter's Reversible Dirt Scoop makes light work of those heavy jobs.

Model type:

30" Reversible Dirt Scoop – Cat. I, 3-pt. hitch, trip dump pan, beveled cutting edge, heavy duty angle iron frame
(Model: DS-30)

Dual Edge Land Graders



Model shown: DEG-72

King Kutter's Dual Edge Land Graders are the perfect tool for driveway and gravel road maintenance and construction. They work to fill potholes and low spots, and redistribute material to achieve the perfect roadway surface. The Cat. I, 3-pt. quick hitch compatible hitch make it easy to hook up and get working fast.

Quick Hitch Compatible

Model types:

Dual Edge Land Graders – Cat. I, 3-pt. quick hitch compatible, two double sided reversible cutting edges, ½" thick replaceable wear pads, heavy duty frame built with 3" x 3" square tubing.
(Models : DEG-60, DEG-72, & DEG-84)



Move Dirt



Dump Dirt



Replaceable Wear Strips



Dual Cutting Edges



Tubular Framed Landscape Rakes



Model shown: TYR-72

King Cutter's Tubular Framed Landscape Rakes are designed with a Cat. 1, 3-pt. quick hitch compatible hitch, great for professional landscapers, farmers, and homeowners. The standard kickstand makes it quick and easy to hookup to a Cat. 1, 3-pt. quick hitch compatible hitch or standard 3-pt hitch. King Cutter's Tubular Frame Landscape Rakes can handle your toughest job for many years to come. The TYR-96 model has extra bracing.

Choose from four sizes:

60", 72", 84" & 96" Tubular Framed Landscape Rakes - Cat. 1, 3-pt. quick hitch compatible hitch, reinforced tubular frame, individual mounted heat treated spring steel tines, 4" x 4" angle beam tine frame, 5 forward and reverse angle settings.

(Models: TYR-60, TYR-72, TYR-84 & TYR-96)

QuickHitch
Compatible



Professional Landscape Rakes



Model shown: YR-G-72

King Cutter's Professional Landscape Rakes are ideal for professional contractors and farmers for those demanding jobs where not just any tool will do. The industrial tube frame with a Cat. 1, 3-pt. quick hitch compatible hitch is ideal for use with most Cat 1 quick hitch systems. So whether you are removing debris before laying sod, or renovating a driveway, this tool is ideal for you.

Choose from four sizes:

60", 72", 84" & 96" Professional Landscape Rakes - Cat. 1, 3-pt. quick hitch compatible hitch, industrial tube frame, individual mounted heat treated spring steel tines, 4" x 4" angle beam tine frame, 5 forward and reverse angle settings.

(Models: YR-G-60, YR-G-72, YR-G-84, & YR-G-96)

QuickHitch
Compatible



Tubular Frame with Gussets



Patented Kick Stand



Easy Angle Adjustment



Heat Treated Spring Steel Tines





Model shown: BB-72

King Kutter's box blades are designed for the farmer, contractor, and professional landscaper in mind. All feature an all welded "A" frame that is Cat. 1 quick hitch compatible with a clevis hitch. The Professional Box Blades has extra gussets for added strength. The Hinged Back Box Blade has a rear cutting edge that will hinge upward to prevent soil build up and allows for a deeper penetration. It also features 3/8" thick endplates for additional strength.

Standard Box Blades

Choose from six sizes:

48" - 96" Box Blades - all welded, Cat. 1 quick hitch compatible 3-pt. hitch, replaceable ripper teeth, formed self-cleaning moldboard, replaceable cutting edges (front & rear), 4"x4" square box shank housing.

(Models: BB-48, BB-60, BB-66, BB-72, BB-84 & BB-96)



Professional Box Blades

Choose from six sizes:

48" - 96" Heavy, all welded, Cat. 1 quick hitch compatible 3-pt. hitch, replaceable ripper teeth, replaceable cutting edges (front & rear), 4"x4" square box shank housing, clevis-type lower hitch brackets.

(Models: BB-G-48, BB-G-60, BB-G-66, BB-G-72, BB-G-84, & BB-G-96.)



Hinged Back Box Blades

Choose from four sizes:

60" - 96" Heavy, all welded, Cat. 1 quick hitch compatible 3-pt. hitch, replaceable ripper teeth, replaceable cutting edges (front & rear), 4"x4" square box shank housing, clevis-type lower hitch brackets, and hinged rear cutting setting.

(Models: H-BB-60, H-BB-72, H-BB-84, & H-BB-96)



Standard Box Blades



Professional Box Blades



Hinged Back Box Blades



XB Sub-Compact Box Blade



Model shown: BB-48-XB

King Kutter's XB Sub-Compact Box Blade has all of the features you'd expect from a standard box blade, in a sub-compact package. They are great for landscaping, back filling, land leveling, or dirt work. Farmers, homeowners, and landscape professionals will all be happy with an XB Sub-Compact Box Blade from King Kutter.

Model type:

48" XB Sub-Compact Box Blade – Limited Cat. I, 3-pt. hitch, 2" x 4" box tube shank frame, flip up ripper shanks, front & rear cutting edges.
(Model: BB-48-XB)



All Welded A Frame



Two Cutting Edges



Model shown: TYR-60-XB

King Kutter's XB Sub-Compact Landscape Rake is designed with a limited Cat. I, 3-pt. hitch for use with today's sub-compact tractors up to 25 HP. This tool is ideal for homeowners who want to maintain their property or driveway and expect to have all of the features of a larger landscape rake, in a sub-compact package. Gauge Wheels are available.

Model type:

60" XB Sub-Compact Landscape Rake – Limited Cat. I, 3-pt. hitch reinforced tube frame, individual mounted heat treated spring steel teeth, five forward and reverse angle settings.
(Model: TYR-60-XB)



Reinforced Tube Frame



Spring Steel Teeth



Landscape Equipment Specifications

Model	TYR-60	TYR-72	TYR-84	TYR-96	TYR-60-XB
HP Range	17 - 50	17 - 50	17 - 50	17 - 50	Up to 25
Approx. Weight	218 lbs.	250 lbs.	271 lbs.	305 lbs.	191 lbs.
Performance					
Working Width	60"	72"	84"	96"	60"
Rake Height	15"	15"	15"	15"	10"
Rake Angle	5 for. & 5 rev.	5 for. & 5 rev.	5 for. & 5 rev.	5 for. & 5 rev.	5 for. & 5 rev.
Tooth Spacing	1"	1"	1"	1"	1"
No. of Teeth	30	36	42	48	30
Construction					
Frame	Reinforced tube	Reinforced tube	Reinforced tube	Reinforced tube	Reinforced tube
Hitch	Cat. I	Cat. I	Cat. I	Cat. I	Limited Cat. I
Quick Hitch Compatible	Yes	Yes	Yes	Yes	No
Rake Tooth Frame	Angle	Angle	Angle	Angle	Angle
Tooth Size	5/16" x 1"	5/16" x 1"	5/16" x 1"	5/16" x 1"	5/16" x 1"
Tooth Composition	High Carbon Spring Steel	High Carbon Spring Steel	High Carbon Spring Steel	High Carbon Spring Steel	High Carbon Spring Steel
Single Tooth Mount	Yes	Yes	Yes	Yes	Yes
Gauge Wheels	Opt.	Opt.	Opt.	Opt.	

Model	YR-G-60	YR-G-72	YR-G-84	YR-G-96
HP Range	17 - 50	17 - 50	25 - 50	25 - 50
Approx. Weight	223 lbs.	239 lbs.	265 lbs.	290 lbs.
Performance				
Working Width	60"	72"	84"	96"
Rake Height	15"	15"	15"	15"
Rake Angle	5 for. & 5 rev.	5 for. & 5 rev.	5 for. & 5 rev.	5 for. & 5 rev.
Tooth Spacing	1"	1"	1"	1"
No. of Teeth	30	30	42	48
Construction				
Frame	Industrial Tube	Industrial Tube	Industrial Tube	Industrial Tube
Hitch	Cat. I	Cat. I	Cat. I	Cat. I
Quick Hitch Compatible	Yes	Yes	Yes	Yes
Rake Tooth Frame	Angle	Angle	Angle	Angle
Tooth Size	5/16" x 1"	5/16" x 1"	5/16" x 1"	5/16" x 1"
Tooth Composition	High Carbon Spring Steel	High Carbon Spring Steel	High Carbon Spring Steel	High Carbon Spring Steel
Single Tooth Mount	Yes	Yes	Yes	Yes
Gauge Wheels	Opt.	Opt.	Opt.	Opt.

Model	DEG-60	DEG-72	DEG-84	Model	DS-30
HP Range	35 - 60	35 - 60	35 - 60	HP Range	17 - 40
Approx. Weight	447 lbs.	491 lbs.	540 lbs.	Approx. Weight	269 lbs.
Performance				Performance	
Working Width	60"	72"	84"	Working Width	30"
No. of Cutting Edges	2 Reversible	2 Reversible	2 Reversible	Approx. capacity	9 cu. Ft.
Wear Pads Thickness	1/2" Replaceable	1/2" Replaceable	1/2" Replaceable	Attachment style	Front or Rear
Construction				Dump mechanism	Trip lever
Hitch	Cat. I	Cat. I	Cat. I	Pan cutting edge	Beveled
Quick Hitch Compatible	Yes	Yes	Yes	Construction	
Frame	Flat Steel, Angle, & Sq. Tube	Flat Steel, Angle, & Sq. Tube	Flat Steel, Angle, & Sq. Tube	Hitch	Cat. I
				Frame	Heavy Duty Angle Iron

**Weights are for products only. Does not include packaging material. *Specifications also available at www.kingkutter.com.*



King Kutter Inc.

PO Box 1200

Winfield, AL 35594

205.487.3202

www.kingkutter.com

Quality Rotary Mowers & Farm Equipment

Landscape Equipment Specifications

Model	BB-48 / BB-60	BB-66 / BB-72	BB-84 / BB-96
HP Range	20 - 35	25 - 45	25 - 45
Approx. Weight	372 lbs. / 441 lbs.	471 lbs. / 500 lbs.	550 lbs. / 604 lbs.
Performance			
Working Width	48" / 60"	66" / 72"	84" / 96"
No. of Scarifier Shanks	4 / 5	5 / 6	6 / 7
No. of Depth Positions	4	4	4
Shank points	Replaceable	Replaceable	Replaceable
Construction			
Cutting edge	(2) 1/2" x 6"	(2) 1/2" x 6"	(2) 1/2" x 6"
Cutting edge construction	(2) Rev. double bevel	(2) Rev. double bevel	(2) Rev. double bevel
Hitch	Cat. I	Cat. I	Cat. I
Lower Hitch Links	Pin	Pin	Pin
Quick Hitch Compatible	Yes	Yes	Yes
End plate thickness	1/4"	1/4"	1/4"
Moldboard height	17 1/2"	17 1/2"	17 1/2"
Shank, Main Frame	1/4" x 4" x 4"	1/4" x 4" x 4"	1/4" x 4" x 4"
Box Length	24"	24"	24"
Box Height	17"	17"	17"
Hitch Frame	1/2" bar w/ brace arms	1/2" bar w/ brace arms	1/2" bar w/ brace arms

Model	BB-G-48	BB-G-60 / BB-G-66 / BB-G-72	BB-G-84 / BB-G-96
HP Range	25 - 50	25 - 50	25 - 50
Approx. Weight	384 lbs.	447 lbs. / 479 lbs. / 510 lbs.	573 lbs. / 670 lbs.
Performance			
Working Width	48"	60" / 66" / 72"	84" / 96"
No. of Scarifier Shanks	4	5 / 5 / 6	6 / 7
No. of Depth Positions	4	4	4
Shank points	Replaceable	Replaceable	Replaceable
Construction			
Cutting edge	(2) 1/2" x 6"	(2) 1/2" x 6"	(2) 1/2" x 6"
Cutting edge construction	(2) Rev. double bevel	(2) Rev. double bevel	(2) Rev. double bevel
Hitch	Cat. I	Cat. I	Cat. I
Lower Hitch Links	Clevis type	Clevis type	Clevis type
Quick Hitch Compatible	Yes	Yes	Yes
End plate thickness	1/4"	1/4"	1/4"
Moldboard height	17 1/2"	17 1/2"	17 1/2"
Shank, Main Frame	1/4" x 4" x 4"	1/4" x 4" x 4"	1/4" x 4" x 4"
Box Length	24"	24"	24"
Box Height	17"	17"	17"
Hitch Frame	3/8" Plate w/ bracing	3/8" Plate w/ bracing	3/8" Plate w/ bracing

Model	H-BB-60 / H-BB-72	H-BB-84 / H-BB-96	BB-48-XB
HP Range	25 - 50	25 - 50	Up to 25 HP
Approx. Weight	502 lbs. / 565 lbs.	622 lbs. / 685 lbs.	292 lbs.
Performance			
Working Width	60" / 72"	84" / 96"	48"
No. of Scarifier Shanks	5 / 6	6 / 7	3
No. of Depth Positions	4	4	1
Shank points	Replaceable	Replaceable	Replaceable
Construction			
Cutting edge	(2) 1/2" x 6"	(2) 1/2" x 6"	(2) 3/8" x 3"
Cutting edge construction	(2) Reversible double bevel	(2) Reversible double bevel	(2) Single bevel
Hitch	Cat. I	Cat. I	Limited Cat. I
Lower Hitch Links	Clevis type	Clevis type	Pin
Quick Hitch Compatible	Yes	Yes	No
End plate thickness	3/8"	3/8"	1/4"
Moldboard height	17 1/2"	17 1/2"	15"
Shank, Main Frame	1/4" x 4" x 4"	1/4" x 4" x 4"	2" x 4" box tubing
Box Length	24"	24"	20"
Box Height	17"	17"	15"
Hitch Frame	3/8" Plate w/ bracing	3/8" Plate w/ bracing	All welded

**Weights are for products only. Does not include packaging material.*

**Specifications also available at www.kingkutter.com.*

King Kutter Inc.
PO Box 1200
Winfield, AL 35594
205.487.3202
www.kingkutter.com



Quality Rotary Mowers & Farm Equipment

King Kutter, Inc. reserves the right to change model numbers, optional equipment and product specifications without notice.

REV. 06_2015_LE